Bosch Communications Systems Get your message across, effectively.



Speakers

Ceiling Speakers – Exceptional sound clarity

A complete range of loudspeakers suitable for both speech and music reproduction in shops, departmental stores, schools, sports halls, hotels, restaurants and all other public address applications.



Unique Features

- Easy to install with spring-loaded mounting clamps
- Power handling capacity 6 Watts / 4 Watts
- Excellent frequency response
- High sound pressure level
- Wide opening angle
- In-built 100V line matching transformer
- Contemporary aesthetic grill design
- Compact size
- Optimised for music & speech applications
- Ideal for mounting on false ceilings

Technical Specifications

	LBD 8353/10	LBD 8352/10	LBD 8351/10	LBD 0606/10
Power handling capacity	6 Watts (6-3-1.5)	6 Watts (6-3-1.5)	4 Watts (4-2-1)	6 Watts (6-3-1.5)
Sound pressure level (max.)	96dB	96dB	93dB	98dB
Effective frequency range	70-15000Hz	70-10000Hz	300-15000Hz	80-16000Hz
Rated input voltage	100 Volts	100 Volts	100 Volts	100 Volts
Rated impedance	1667	1667	1667	1667
Colour	IFB white	IFB white	IFB white	IFB white
Weight (approx.)	750 Grams	600 Grams	500 Grams	800 Grams
Mounting	Clamptype	Clamptype	Clamp type	Clamptype
Overall dimensions	210mm Dia. 90mm Height	180mm Dia. 70mm Height	165mm Dia. 65mm Height	200mm Dia. 70mm Height

Tradition of quality and innovation

For over 100 years, the Bosch name has stood for quality and reliability. Bosch Security Systems proudly offers a wide range of fire, intrusion, CCTV, management and communication systems and components to help you find the solution for any application. We are the global supplier of choice for innovative technology backed by the highest level of service and support. When you need solutions you can rely on, choose Bosch.

Bosch Limited, Security Systems Division P.B. No. 3000, Hosur Road Bangalore - 560 030 Tel.: +91 80 4176 8378 Fax: +91 80 4176 8263 E-mail: boschsecuritysystems@in.bosch.com www.boschsecurity.co.in



Security Certified Partner BSCP Stamp

